LUMBER JACK
Everyday Woodworking Solutions

2000W WALLPAPER STRIPPER

WPS2000



USER MANUAL

Please read and retain these instructions before use.

Product Overview



1 Safety Cap
2 Carry Handle
3 Steam Plate
4 Water Tank
5 Steme Hose

2. Assembly - Connect The Hose

1 Connect hose to water tank



2 Connect hose to steam plate



3 Tighten both fittings securely



Ensure connections are secure before use.

3. Filling The Tank

1 Disconnect from power



2 Remove safety cap slowly



3 Fill with clean water between MIN and MAX markings



4 Do not overfill



4 Refit safety cap securely



4. Operating Instructions

1 Place the unit on a flat, heat resistant surface



2 Connect to power supply



3 Allow unit to heat until steam is produced



4 Score wallpaper before steaming



5 Hold steam plate against wallpaper for approx. 10 seconds



6 Remove loosened wallpaper with a scraper



For stubborn wallpaper, leave the steam plate in place slightly longer

Allow the unit to rest for 15 minutes after every hour of use

5. After Use

1 Switch off and unplug



2 Allow unit to cool fully



3 Empty remaining water



4 Store in a dry location



6. Cleaning & Maintenance

After Each Use

1 Switch off and unplug
2 Allow unit to cool
3 Empty remaining water
4 Wipe clean with a dry cloth



Descaling (Regular Maintenance)



2 Parts Water + 1 Part White Vinegar

Fill the tank with the solution and leave for approx, 1 hour

Rinse thoroughly with clean water



7. Safety Information

- Steam and surfaces become very hot during use.
- Never direct steam at people, pets or electrical equipment.
- Keep children away during operation and cooling.
- Disconnect from mains before filling or maintenance.
- Do not remove the safety cap while pressure remains.
- Wear safety glasses and protective gloves.

Risk of burns from steam and hot water.
For indoor use only. Do not use in the rain or wet conditions.

8. Technical Specifications

Power:	2000W
Voltage:	230V 50Hz
Usage Time:	70-80 Min
Tank Capacity:	4.5L
Hose Length:	3M
Protection Class:	IPX4
Cable Length:	2M
Dimensions:	325 X 255 X 260mm
Weight:	2.0kg

9. Troubleshooting

Problem	Possible Cause / Solution
No Steam	Check power supply and ensure tank has water.
Weak Steam	Allow more time for the unit to heat up or descale the tank.
Poor Stripping Performance	Leave steam plate in place longer rescore wallpaper.
Steam leaking From Connections	Ensure hose is connected and fittings are tightened securely. heat up or descale the tank.

10. Disposal

Do not dispose of electrical equipment with household waste.

Recycle responsibly through approved recycling facilities.

UKCA

1 YEAR 1 WARRANTY

This product is guaranteed for 1 year from the date of purchase against manufacturing defects. Proof of purchase is required.
Visit our websie for full terms and conditions.